

Marquis Cinnamon Cabinet Specifications

① Face Frames

Face Frames are $\frac{3}{4}$ " * $1\frac{1}{2}$ " Solid hardwood Plywood, Frames are mortise and tenons construction reinforced with glue and nails. Frames are dadoed to received cabinet ends, top, and bottoms.

② Tops & Bottoms

Tops and bottom panels are $\frac{1}{2}$ " thick multi-ply hardwood plywood. Tops and bottoms are dadoed into the face frame and end panels. Base bottom panels are $\frac{3}{8}$ " thick.

③ Toe Kicks

Toe kicks shall be $\frac{1}{2}$ " thick hardwood plywood.

④ End Panels

End panels are $\frac{1}{2}$ " thick multi-ply hardwood plywood. All end panels are dadoed into the face frame and recessed $\frac{3}{16}$ ".

⑤ Adjustable Shelves

Adjustable shelves are $\frac{5}{8}$ " thick multi-ply hardwood Plywood. Edge banded with wood tapes. (Exceeds industry standards.)

⑥ Back Panels

5+12 mm thick multi-ply hardwood plywood. Backs are routed, glued and nailed in cabinet. (Exceeds industry standards.)

⑦ Shelf Clips

Shelf clips are 6mm bore with a fluted Metal clips. Shelves are adjustable on $2\frac{1}{2}$ " increments.

⑧ Doors

$\frac{3}{4}$ " Solid Hardwood Miter door styles with straight top raised panels.

⑨ Hinges

Full Overlay, Concealed, 110 degree opening.

⑩ Drawer Boxes

$\frac{5}{8}$ " solid hardwood front, back and 2 sides with $\frac{3}{8}$ " plywood drawer bottoms, Dovetail construction. (Exceeds industry standards.)

⑪ Drawer Glides

Soft Closing Undermount Full Extension Glides. (Exceeds industry standards.)

⑫ Base Corner Brackets

High impact, injection molded plastic.

⑬ Hanging Strips

Hanging strip are $\frac{3}{4}$ " * $1\frac{1}{4}$ " hardwood.

