

New Castle Gray

Cabinet Specifications

1 Face Frames

Face Frames are $\frac{3}{4}$ " * 1 $\frac{1}{2}$ " solid hardwood. Frames are mortise and tenons construction reinforced with glue and nails.Frames are dadoed to received cabinet ends,top, and

Tops & Bottoms

Tops and bottom panels are $\frac{1}{2}$ " thick multi-ply hardwood plywood. Tops and bottoms are dadoed into the face frame and end panels. Base bottom panels are $\frac{3}{8}$ "thick.

Toe Kicks

Toe kicks shall be 1/2" thick hardwood plywood.

(4) End Panels

End panels are ½"thick mutli-ply hardwood plywood. All end panels are dadoed into the face frame and recessed $\frac{3}{16}$. Adjustable Shelves

Adjustable shelves are 3/4" thick multi-ply hardwood Plywood. Edge banded with wood tapes. (Exceeds industry standards.)

(6) Back Panels

Back are ½"thick multi-ply hardwood plywood. Backs are routed, glued and nailed in cabinet. (Exceeds industry standards.)

(7) Shelf Clips

Shelf clips are 6mm bore with a fluted Metal clips. Shelved are adjustable on $2\frac{1}{2}$ increments.

 $\textcircled{8} \frac{Doors}{Solid \ wood \ stiles \ \& \ Veneer \ raised \ panel \ door \ and \ drawer \ front.}$

 \odot Hinges Full Overlay , Concealed, 110 degree opening, with soft closing dampers .

 $\frac{5}{8}$ solid hardwood front, back and 2 sides with $\frac{3}{8}$ plywood drawer bottoms, Dovetail construction. (Exceeds industry standards.)

Drawer Glides

Soft Closing Undermount Full Extension Glides ..(Exceeds industry standards)

Base Corner Brackets

High impact, injection molded plastic .

Hanging Strips

(13) Hanging strip are $\frac{3}{4}$ *1 $\frac{1}{4}$ " hardwood.



