

### **Pacific Gray**

### **Cabinet Specifications**

# 1 Face Frames

Face Frames are  $\frac{3}{4}$  \* 1  $\frac{1}{2}$  solid hardwood. Frames are mortise and tenons construction reinforced with glue and nails.Frames are dadoed to received cabinet ends,top, and bottoms.

 $\textcircled{\ } \underbrace{ \ } \frac{ \text{Tops \& Bottoms} }{ \text{Tops and bottom panels are } \frac{1}{2} \text{'thick multi-ply hardwood} } }$ plywood . Tops and bottoms are dadoed into the face frame and end panels. Base bottom panels are  $\frac{3}{8}$ "thick.

 $\Im \frac{\text{Toe Kicks}}{\text{Toe kicks shall be } \frac{1}{2}^{n} \text{ thick hardwood plywood }}.$ 

## (4) End Panels

2

End panels are  $\frac{1}{2}$  "thick mutli-ply hardwood plywood. All end panels are dadoed into the face frame and recessed  $\frac{3}{16}$ . S Adjustable Shelves Adjustable shelves are <sup>5</sup>/<sub>8</sub>" thick multi-ply hardwood Plywood. Edge banded with wood tapes. (Exceeds industry standards.)

## 6 Back Panels

Back are  $\frac{1}{2}$  "thick multi-ply hardwood plywood. Backs are routed, glued and nailed in cabinet. (Exceeds industry standards.)

# The Shelf Clips

- Shelf clips are 6mm bore with a fluted Metal clips. Shelved are adjustable on  $2\frac{1}{2}$  increments.
- (8) Doors  $\frac{3}{4}$ "HDF door styles with flat panels.

### Hinges


 Full Overlay , Concealed, 110 degree opening, with soft closing dampers .


#### Drawer Boxes (10)

- $\frac{5}{8}$  solid hardwood front, back and 2 sides with  $\frac{3}{8}$  plywood drawer bottoms, Dovetail construction. (Exceeds industry standards.)
- Drawer Glides Soft Closing Undermount Full Extension Glides .. (Exceeds industry standards)

#### Base Corner Brackets (12)

- High impact, injection molded plastic .
- Hanging Strips (13) Hanging strip are  $\frac{3}{4}$  \*1 $\frac{1}{4}$  hardwood.





www.ghicabinets.com

13 8

(9)