

## **Rustic Walnut**

## **Cabinet Specifications**

1 Face Frames

Face Frames are  $\frac{3}{4}$  \* 1  $\frac{1}{2}$  solid hardwood. Frames are mortise and tenons construction reinforced with glue and nails. Frames are dadoed to received cabinet ends, top, and

Tops & Bottoms

1/2" thick multi-ply hardwood plywood . Tops and bottoms are dadoed into the face frame and end panels. Base bottom

Toe Kicks

 $\frac{1}{2}$ " thick hardwood plywood.

(4) End Panels

½"thick mutli-ply hardwood plywood. All end panels are dadoed into the face frame and recessed  $\frac{3}{16}$ .

Adjustable Shelves

3/4" thick multi-ply hardwood Plywood. Edge banded with wood tapes.(Exceeds industry standards.)

6 Back Panels

½" thick multi-ply hardwood plywood. Backs are routed, glued and nailed in cabinet. (Exceeds industry standards.)

on  $2\frac{1}{2}$  increments.

® Doors 3/4" Solid hard wood door stiles with flat central panel, shaker.

(9) Full Overlay , Concealed, 110 degree opening, with soft closing dampers.

 $\frac{3}{4}$ "solid hardwood front, back and 2 sides with  $\frac{3}{8}$ " plywood drawer bottoms, Dovetail construction. (Exceeds industry standards.)

Drawer Glides

Soft Closing Undermount Full Extension Glides .. (Exceeds industry standards)

Base Corner Brackets

High impact, injection molded plastic .

Hanging Strips

 $\frac{3}{4}$ "\*1 $\frac{1}{4}$ "hardwood.



